

## Technical specifications

Test	Test method	Characteristics
Formaldehyde emission	EN 717-1	E1, < 0,05 ppm
Resistance to staining	EN 438-2	group 1+2: level 5 group 3: level 4
Light fastness	EN ISO 105-B02 EN ISO 105-A02	> level 6 blue wool scale > level 4 grey scale
Fire resistance	EN 13501-1	Ignites with difficulty, at least C <sub>f</sub> -s1
Height difference between connected elements	ISO 24337	average : ≤ 0,10 mm max: ≤ 0,15 mm
Edge straightness	ISO 24337	≤ 0,3 mm/m
Openings between connected elements	ISO 24337	average: ≤ 0,15 mm max: ≤ 0,20 mm
Static indentation	EN ISO 24343-1	≤ 0,2 mm
Microscratch resistance	EN 16094	≤ MSR - A2
Abrasion resistance	EN 15468, App. A	AC4, ≥ 3.000 cycles
Impact resistance	EN 13329, App. H	≥ 1.200 mm
Thickness swelling	ISO 24336	≤ 18,0 %
Castor chair test	EN 425	25.000 cycles
Classification	EN ISO 10874	
Thermal resistance	EN 12667	0,0556 (m²K)/W

## Characteristics

-  low maintenance & hard-wearing
-  largely resistant to cigarette burns
-  durable & impact resistant
-  stain resistant
-  non-fading and retain their brilliance over many years
-  abrasion resistant
-  flame resistant
-  comfortable underfoot
-  well-suited for installation over subfloor heating
-  produced from natural sustainable raw materials

## Product specifications

<b>Surface</b>	High gloss or Supermatt
<b>Panel size</b>	1220 x 610 x 8 mm
<b>Box</b>	4 panels = 2,977 sqm
<b>Pallet</b>	89,304 sqm = 678 kg 30 boxes
<b>Utility class</b>	32   AC 4



## Technical specifications

Test	Test method	Characteristics
Formaldehyde emission	EN 717-1	E1, < 0,05 ppm
Resistance to staining	EN 438-2	group 1+2: level 5 group 3: level 4
Light fastness	EN ISO 105-B02 EN ISO 105-A02	> level 6 blue wool scale > level 4 grey scale
Fire resistance	EN 13501-1	Ignites with difficulty, at least C <sub>f</sub> -s1
Height difference between connected elements	ISO 24337	average : ≤ 0,10 mm max: ≤ 0,15 mm
Edge straightness	ISO 24337	≤ 0,3 mm/m
Openings between connected elements	ISO 24337	average: ≤ 0,15 mm max: ≤ 0,20 mm
Static indentation	EN ISO 24343-1	≤ 0,2 mm
Microscratch resistance	EN 16094	≤ MSR - A2
Abrasion resistance	EN 15468, App. A	AC4, ≥ 3.000 cycles
Impact resistance	EN 13329, App. H	≥ 1.200 mm
Thickness swelling	ISO 24336	≤ 18,0 %
Castor chair test	EN 425	25.000 cycles
Classification	EN ISO 10874	
Thermal resistance	EN 12667	0,0556 (m²K)/W

## Characteristics

-  low maintenance & hard-wearing
-  largely resistant to cigarette burns
-  durable & impact resistant
-  stain resistant
-  non-fading and retain their brilliance over many years
-  abrasion resistant
-  flame resistant
-  comfortable underfoot
-  well-suited for installation over subfloor heating
-  produced from natural sustainable raw materials

## Special properties

-  high gloss surface
-  V-Groove

## Product specifications

<b>Surface</b>	High gloss or Supermatt
<b>Panel size</b>	610 x 610 x 8 mm
<b>Box</b>	6 panels = 2,233 sqm
<b>Pallet</b>	49,13 sqm = 370 kg
	22 boxes
<b>Utility class</b>	32   AC 4



## Technical specifications

Test	Test method	Characteristics
Formaldehyde emission	EN 717-1	E1, < 0,05 ppm
Resistance to staining	EN 438-2	group 1+2: level 5 group 3: level 4
Light fastness	EN ISO 105-B02 EN ISO 105-A02	> level 6 blue wool scale > level 4 grey scale
Fire resistance	EN 13501-1	Ignites with difficulty, at least C <sub>f</sub> -s1
Height difference between connected elements	ISO 24337	average : ≤ 0,10 mm max: ≤ 0,15 mm
Edge straightness	ISO 24337	≤ 0,3 mm/m
Openings between connected elements	ISO 24337	average: ≤ 0,15 mm max: ≤ 0,20 mm
Static indentation	EN ISO 24343-1	≤ 0,2 mm
Microscratch resistance	EN 16094	≤ MSR - A2
Abrasion resistance	EN 15468, App. A	AC4, ≥ 3.000 cycles
Impact resistance	EN 13329, App. H	≥ 1.200 mm
Thickness swelling	ISO 24336	≤ 18,0 %
Castor chair test	EN 425	25.000 cycles
Classification	EN ISO 10874	
Thermal resistance	EN 12667	0,0556 (m²K)/W

## Characteristics

-  low maintenance & hard-wearing
-  largely resistant to cigarette burns
-  durable & impact resistant
-  stain resistant
-  non-fading and retain their brilliance over many years
-  abrasion resistant
-  flame resistant
-  comfortable underfoot
-  well-suited for installation over subfloor heating
-  produced from natural sustainable raw materials

## Special properties

-  high gloss surface
-  V-Groove

## Product specifications

<b>Surface</b>	High gloss
<b>Panel size</b>	1.220 x 193 x 8 mm
<b>Box</b>	8 panels = 1,884 sqm
<b>Pallet</b>	67,81 sqm = 510 kg
	36 boxes
<b>Utility class</b>	32   AC 4



## Technical specifications

Test	Test method	Characteristics
Formaldehyde emission	EN 717-1	E1, < 0,05 ppm
Resistance to staining	EN 438-2	group 1+2: level 5 group 3: level 4
Light fastness	EN ISO 105-B02 EN ISO 105-A02	> level 6 blue wool scale > level 4 grey scale
Fire resistance	EN 13501-1	Ignites with difficulty, at least C <sub>f</sub> -s1
Height difference between connected elements	ISO 24337	average : ≤ 0,10 mm max: ≤ 0,15 mm
Edge straightness	ISO 24337	≤ 0,3 mm/m
Openings between connected elements	ISO 24337	average: ≤ 0,15 mm max: ≤ 0,20 mm
Static indentation	EN ISO 24343-1	≤ 0,2 mm
Microscratch resistance	EN 16094	≤ MSR - A2
Abrasion resistance	EN 15468, App. A	AC4, ≥ 3.000 cycles
Impact resistance	EN 13329, App. H	≥ 1.200 mm
Thickness swelling	ISO 24336	≤ 18,0 %
Castor chair test	EN 425	25.000 cycles
Classification	EN ISO 10874	
Thermal resistance	EN 12667	0,0556 (m²K)/W

## Characteristics

-  low maintenance & hard-wearing
-  largely resistant to cigarette burns
-  durable & impact resistant
-  stain resistant
-  non-fading and retain their brilliance over many years
-  abrasion resistant
-  flame resistant
-  comfortable underfoot
-  well-suited for installation over subfloor heating
-  produced from natural sustainable raw materials

## Special properties

-  high gloss surface
-  V-Groove

## Product specifications

<b>Surface</b>	High gloss
<b>Panel size</b>	644 x 310 x 8 mm
<b>Box</b>	10 panels = 1,996 sqm
<b>Pallet</b>	83,83 sqm = 620 kg
	42 boxes
<b>Utility class</b>	32   AC 4



## Technical specifications

Test	Test method	Characteristics
Formaldehyde emission	EN 717-1	E1, < 0,05 ppm
Resistance to staining	EN 438-2	group 1+2: level 5 group 3: level 4
Light fastness	EN ISO 105-B02 EN ISO 105-A02	> level 6 blue wool scale > level 4 grey scale
Fire resistance	EN 13501-1	Ignites with difficulty, at least C <sub>f</sub> -s1
Height difference between connected elements	ISO 24337	average : ≤ 0,10 mm max: ≤ 0,15 mm
Edge straightness	ISO 24337	≤ 0,3 mm/m
Openings between connected elements	ISO 24337	average: ≤ 0,15 mm max: ≤ 0,20 mm
Static indentation	EN ISO 24343-1	≤ 0,2 mm
Microscratch resistance	EN 16094	≤ MSR - A2
Abrasion resistance	EN 15468, App. A	AC4, ≥ 3.000 cycles
Impact resistance	EN 13329, App. H	≥ 1.200 mm
Thickness swelling	ISO 24336	≤ 18,0 %
Castor chair test	EN 425	25.000 cycles
Classification	EN ISO 10874	
Thermal resistance	EN 12667	0,0556 (m²K)/W

## Characteristics

-  low maintenance & hard-wearing
-  largely resistant to cigarette burns
-  durable & impact resistant
-  stain resistant
-  non-fading and retain their brilliance over many years
-  abrasion resistant
-  flame resistant
-  comfortable underfoot
-  well-suited for installation over subfloor heating
-  produced from natural sustainable raw materials

## Special properties

-  high gloss surface
-  V-Groove

## Product specifications

<b>Surface</b>	High gloss or Supermatt
<b>Panel size</b>	810 x 400 x 8 mm
<b>Box</b>	8 panels = 2,592 sqm
<b>Pallet</b>	103,68 sqm = 770 kg
	40 boxes
<b>Utility class</b>	32   AC 4



## Technical specifications

Test	Test method	Characteristics
Formaldehyde emission	EN 717-1	E1, < 0,05 ppm
Resistance to staining	EN 438-2	group 1+2: level 5 group 3: level 4
Light fastness	EN ISO 105-B02 EN ISO 105-A02	> level 6 blue wool scale > level 4 grey scale
Fire resistance	EN 13501-1	Ignites with difficulty, at least C <sub>f</sub> -s1
Height difference between connected elements	ISO 24337	average : ≤ 0,10 mm max: ≤ 0,15 mm
Edge straightness	ISO 24337	≤ 0,3 mm/m
Openings between connected elements	ISO 24337	average: ≤ 0,15 mm max: ≤ 0,20 mm
Static indentation	EN ISO 24343-1	≤ 0,2 mm
Microscratch resistance	EN 16094	≤ MSR - A2
Abrasion resistance	EN 15468, App. A	AC4, ≥ 3.000 cycles
Impact resistance	EN 13329, App. H	≥ 1.200 mm
Thickness swelling	ISO 24336	≤ 18,0 %
Castor chair test	EN 425	25.000 cycles
Classification	EN ISO 10874	
Thermal resistance	EN 12667	0,0556 (m²K)/W

## Characteristics

-  low maintenance & hard-wearing
-  largely resistant to cigarette burns
-  durable & impact resistant
-  stain resistant
-  non-fading and retain their brilliance over many years
-  abrasion resistant
-  flame resistant
-  comfortable underfoot
-  well-suited for installation over subfloor heating
-  produced from natural sustainable raw materials

## Special properties

-  high gloss surface
-  V-Groove

## Product specifications

<b>Surface</b>	High gloss or Supermatt
<b>Panel size</b>	1220 x 610 x 8 mm
<b>Box</b>	4 panels = 2,977 sqm
<b>Pallet</b>	89,304 sqm = 678 kg
	30 boxes
<b>Utility class</b>	32   AC 4

## Technical specifications

Test	Test method	Characteristics
Formaldehyde emission	EN 717-1	E1, < 0,05 ppm
Resistance to staining	EN 438-2	group 1+2: level 5 group 3: level 4
Light fastness	EN ISO 105-B02 EN ISO 105-A02	> level 6 blue wool scale > level 4 grey scale
Fire resistance	EN 13501-1	Ignites with difficulty, at least C <sub>f</sub> -s1
Height difference between connected elements	ISO 24337	average : ≤ 0,10 mm max: ≤ 0,15 mm
Edge straightness	ISO 24337	≤ 0,3 mm/m
Openings between connected elements	ISO 24337	average: ≤ 0,15 mm max: ≤ 0,20 mm
Static indentation	EN ISO 24343-1	≤ 0,2 mm
Microscratch resistance	EN 16094	≤ MSR - A2
Abrasion resistance	EN 15468, App. A	AC4, ≥ 3.000 cycles
Impact resistance	EN 13329, App. H	≥ 1.200 mm
Thickness swelling	ISO 24336	≤ 18,0 %
Castor chair test	EN 425	25.000 cycles
Classification	EN ISO 10874	
Thermal resistance	EN 12667	0,0556 (m²K)/W

## Characteristics

-  low maintenance & hard-wearing
-  largely resistant to cigarette burns
-  durable & impact resistant
-  stain resistant
-  non-fading and retain their brilliance over many years
-  abrasion resistant
-  flame resistant
-  comfortable underfoot
-  well-suited for installation over subfloor heating
-  produced from natural sustainable raw materials

## Product specifications

<b>Surface</b>	Supermatt
<b>Panel size</b>	644 x 310 x 8 mm
<b>Box</b>	10 panels = 1,996 sqm
<b>Pallet</b>	83,83 sqm = 620 kg 42 boxes
<b>Utility class</b>	32   AC 4